Claim Amendments:

Please amend the claims as indicated:

---

1. (Cancel)

2. (Currently Amended) The transceiving unit as recited in ~~claim 1~~claim 7 wherein the baseband processor comprises first and second means for supporting concurrent voice and data communications.

3. (Currently Amended) The transceiving unit as recited in ~~claim 1~~claim 7 wherein each time slot comprises a 32-bit preamble for synchronization, a 64 bit A-field for signaling and a B-field comprising 320 bits and 4 bit for CRC.

4. (Cancel)

5. (Cancel)

6. (Cancel)

7. (Currently Amended) A transceiving unit for wireless communications over the industrial-scientific-medical (ISM) spectrum comprising :~~The transceiving unit as recited in claim 6 wherein~~

(a) an RF sub-module for transceiving information in a 2.4 to 2.5 GHz band; and,

(b) a processor coupled and adapted to provide time slot and frame timing to the RF sub-module, wherein, at least seventy-five hopping frequencies ranging between 2401.122 MHz to 2479.813 MHz and a minimum hop rate of 2.5 hops per second are maintained, the seventy five hopping frequencies are spaced 1.063 MHz apart and each of the seventy-five hopping frequencies support a ten-millisecond frame having ~~the sixteen~~sixteen time ~~slots~~ slots that~~preferably~~ change carrier signals ~~after two~~after a predetermined number of consecutive frames.

8. (Original) The transceiving unit as recited in claim 7 wherein unequal amounts of time slots are allocated between voice and data communications.

9. (Original) The transceiving unit as recited in claim 7 wherein time slots 1,2,3 and 9, 10, 11 are allocated for data communications and time slots 4, 5, 6 and 12, 13, 14 are allocated for voice communications. 7, 8, 15, 16

10. (Original) The transceiving unit as recited in claim 9 wherein time slot 8 is allocated to program the transmit carrier frequency and slot 16 is allocated to program the receive carrier frequency.

11. (Previously Presented) The transceiving unit as recited in claim 9 wherein time slots 1,2,3 and 9, 10, 11 allocate 80 bits in a B field of each time slot to a Forward Error Correction Code (FECC).

12. (Previously Presented) The transceiving unit as recited in claim 9 wherein time slots 4, 5, 6 and 12, 13, 14 allocate an entire B field of each time slot to voice information.

13. (Canceled)

14. (Canceled)

15. (Canceled)

16. (Canceled)

17. (Currently amended) A wireless communications method over the industrial-scientific-medical (ISM) spectrum comprising the steps of: ~~The method as recited in claim 16 wherein~~

(a) transceiving information in a 2.4 to 2.5 GHz band to support concurrent voice and data information packetized into plural time slots within a time frame, each of the plural time slots has a different one of the at least seventy-five carrier frequencies,

and each of the plural time slots changes to a different one of the at least seventy-five carrier frequencies after a predetermined number of consecutive ~~frames.~~frames; and

(b) a processor to provide time slot and frame timing for step (a) such that at least seventy-five carrier frequencies between 2.4 GHz and 2.4835 GHz and a minimum hop rate of 2.5 hops per second are maintained.

18. (Original) The method as recited in claim 16 further comprising the step of providing time slot and frame timing such that seventy-five carrier frequencies are programmed ranging between 2401.122 MHz to 2479.813 MHz and spaced 1.063 MHz apart.

19. (Previously Presented) The method as recited in claim 18 further comprising the step of providing time slot and frame timing such that each of the seventy-five carrier frequencies supports a ten-millisecond frame.

20. (Currently Amended) A system for wireless communications over the industrial-scientific-medical spectrum comprising:

(a) a base station unit having a first transceiving unit;

(b) a cordless personal access device having a second transceiving unit; and,

(c) the first and second transceiving units including:

(i) an RF sub-module for transceiving information in a 2.4 to 2.5 GHz band; and,

(ii) a ~~DECT baseband~~ processor coupled and adapted to provide time slot and frame timing to the RF sub-module ~~such that~~wherein at least seventy-five carrier frequencies between 2.4 GHz and 2.4835 GHz and a minimum hop rate of 2.5 hops per second are maintained and to support a frame that has sixteen time slots that change carrier channels after two consecutive frames.

21. (New) A method comprising:

(a) determining a current frame of at least seventy five frames to transmit data to a target device, each frame of the at least seventy five frames residing at a unique carrier range in a 2.4 to 2.5 GHz band;

(b) determining data to be transmitted over a plurality of time slots of the current frame;

(c) determining a different frame of the at least seventy-five frames, wherein the different frame and the current frame are not the same frame; and

(d) identifying the different frame as the current frame after a predetermined number of frame cycles, and repeating (b), (c) and (d).

22. (New) The method of claim 21 wherein the plurality of time slots is sixteen time slots.

23. (New) The method of claim 22, wherein each frame of the at least seventy five frames is spaced 1.063 MHz apart.

24. (New) The method of claim 23, wherein each frame has a ten-millisecond duration.

25. (New) The method of claim 21, wherein each frame of the at least seventy five frames is spaced 1.063 MHz apart.

26. (New) The method of claim 21, wherein each frame has a ten-millisecond duration.

27. (New) The method of claim 7, wherein the predetermined number of consecutive frames is two.